

Serial No. 09/938,793  
Proposed Amendments  
Page 4

**REMARKS**

In view of the amendments set forth above, the Applicant respectfully requests allowance of the pending claims. If the Examiner believes that a telephonic interview will help speed this application toward issuance, the Examiner is invited to contact the undersigned at the telephone number listed below.

Respectfully submitted,

Date: April 30, 2003



Ralph A. Graham  
Reg. No. 47,607  
Fletcher, Yoder & Van Someren  
P.O. Box 692289  
Houston, TX 77269-2289  
(281) 970-4545

**CORRESPONDENCE ADDRESS**  
ALLEN-BRADLEY COMPANY, LLC  
Patent Department/704P Floor 8 T-29  
1201 South Second Street  
Milwaukee, Wisconsin 53204  
Attention: Mr. Alexander Gerasimow  
Phone: (414) 382-2000

Serial No. 09/938,793  
Proposed Amendments  
Page 5

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

Please cancel claim 11 without prejudice.

Please amend claims 1, 2, 7, 13, and 22 as follows:

1. (Twice Amended) A bearing assembly, comprising:  
a bearing insert;  
a bearing housing adapted to house the bearing insert;  
a cover removably securable to the bearing housing; and  
a rotatable flinger secured to the cover, the rotatable flinger ~~having comprising:~~  
a first opening therethrough, the first opening being adapted to receive ~~a~~ the  
rotatable shaft and to enable the rotatable flinger to form a compression seal against the  
rotatable shaft; ~~and~~  
<sup>36</sup> an outer flange disposed external to the <sup>24</sup> cover to fling material that comes  
into contact with the outer flange away from the bearing assembly.
2. (Amended) The bearing assembly as recited in claim 1, wherein the  
rotatable flinger has an inner flange ~~and an outer flange~~, the inner and outer flanges having a  
greater diameter than a second opening through the cover, the inner and outer flanges  
cooperating with a portion of the cover surrounding the second opening to secure the  
rotatable flinger to the cover.
7. (Amended) The bearing assembly as recited in claim 16, wherein the  
bearing insert comprises a plurality of roller bearings.

13. (Amended) A sealing assembly for forming a seal between a bearing  
assembly and a rotatable shaft, comprising:  
a cover removably securable to a bearing housing; and

Serial No. 09/938,793  
Proposed Amendments  
Page 6

a rotatable member securable to the cover and adapted to receive the rotatable shaft therethrough, the rotatable member being configured to form a seal against the rotatable shaft and to rotate therewith to fling liquids or solids that come into contact with the rotatable member away from the cover-bearing assembly.

22. (Amended) A method of assembling a bearing assembly for supporting a rotatable shaft, comprising the acts of:

engaging a rotatable shaft with a flinger operable to rotate with the rotatable shaft and form a compression seal therewith;

positioning the rotatable shaft through a portion of a bearing insert;

rotatably securing the flinger to a removable cover by disposing the cover between an inner flanged portion of the flinger and an outer flanged portion of the flinger; and

securing the cover to a bearing housing.